

3010 Style Time Zone Clock



3010C - 1.8" time,
1.2" zone labels



3010I - 2.5" time,
1.2" zone labels
B25G Option



3010C - 1.8" time,
1.2" zone labels
B25Y Option



3010F - 1.8" time,
1.2" zone labels
G25R Option

The 3010 series time zone clocks have bar-segment LED time displays with a ten character dot matrix digital zone labels. In many 3010 models, the clock can display up to 24 time zones through page flipping. For Example, a six zone clock can show four pages of time zone information. Likewise, a four zone unit can show six pages.

Each 3010 clock comes standard with an OCXO oscillator, which is accurate to .06 seconds per year.

For easy clock management, an infrared (IR) remote control is included with every 3010 model. You can specify a radio (RF) remote, if preferred for no additional charge. Every 3010 model includes your choice of an Ethernet or USB interface for easy time zone parameter control.

Features:

- OCXO oscillator accurate to .06 seconds per year
- 1.8", 2.5" or 4.0" red bar segment LEDs for displaying time* (blue & green optional)
- 1.2" or 2.0" red 10 character alpha numeric dot matrix LEDs for displaying zone names* (blue, green & yellow optional)
- Models that display from 1 to 13 separate time zones
- Zone flipping feature that allows up to 24 zones in a single clock*
- 12 or 24 hour format
- DST and incremental time zone offsets supported
- PC Interface: USB Interface
- IR remote control standard or optional RF remote
- Black brushed Aluminum frame
- Multiple cord lengths available
- US, British, Australian or European plugs
- 100-240 VAC. 50-60 cycle power
- Available on GSA, contract GS-02F-0030U

*See individual model number for details.



Oven Controlled Crystal Oscillator (OCXO)

- Accurate to 2 PPB (parts per Billion) or .06 seconds per year or about 1 second in 20 years.
- 1 thousand times more accurate than most competing clocks
- Eliminates the need for GPS or Network time synchronization for

3010 Style Time Zone Clocks

Model	Physical Positions	Maximum		Displays		Viewing Distance	Dimensions		
		Pages	Zones	Time	Label		H	W	D
3010R	2	12	24	1.8"	1.2"	40 ft.	14.25	15.25	3.25
3010A	3	8	24	1.8"	1.2"	40 ft.	21.25	15.25	3.25
3010B	4	6	24	1.8"	1.2"	40 ft.	28.25	15.25	3.25
3010C	5	4	20	1.8"	1.2"	40 ft.	35.25	15.25	3.25
3010D	6	4	24	1.8"	1.2"	40 ft.	42.25	15.25	3.25
3010E	7	3	21	1.8"	1.2"	40 ft.	49.25	15.25	3.25
3010F	8	3	24	1.8"	1.2"	40 ft.	56.25	15.25	3.25
3010P	9	2	18	1.8"	1.2"	40 ft.	63.25	15.25	3.25
3010Q	10	2	20	1.8"	1.2"	40 ft.	70.25	15.25	3.25
3010S	11	2	22	1.8"	1.2"	40 ft.	77.25	15.25	3.25
3010U	12	2	24	1.8"	1.2"	40 ft.	84.25	15.25	3.25
3010W	13	1	13	1.8"	1.2"	40 ft.	91.25	15.25	3.25
3010T	2	12	24	2.5"	1.2"	75 ft.	16.25	15.25	3.25
3010G	3	8	24	2.5"	1.2"	75 ft.	24.25	15.25	3.25
3010H	4	6	24	2.5"	1.2"	75 ft.	32.25	15.25	3.25
3010I	5	4	20	2.5"	1.2"	75 ft.	40.25	15.25	3.25
3010J	6	4	24	2.5"	1.2"	75 ft.	48.25	15.25	3.25
3010K	7	3	21	2.5"	1.2"	75 ft.	56.25	15.25	3.25
3010L	8	3	24	2.5"	1.2"	75 ft.	64.25	15.25	3.25
3010X	9	2	18	2.5"	1.2"	75 ft.	72.25	15.25	3.25
3010Y	10	2	20	2.5"	1.2"	75 ft.	80.25	15.25	3.25
3010Z	11	2	22	2.5"	1.2"	75 ft.	88.25	15.25	3.25
3010AA	12	2	24	2.5"	1.2"	75 ft.	96.25	15.25	3.25
3010V	2	12	24	4.0"	2.0"	100 ft.	24.25	24.25	3.25
3010M	3	8	24	4.0"	2.0"	100 ft.	36.25	24.25	3.25
3010N	4	6	24	4.0"	2.0"	100 ft.	48.25	24.25	3.25
3010O	5	4	20	4.0"	2.0"	100 ft.	60.25	24.25	3.25
3010AB	6	4	24	4.0"	2.0"	100 ft.	72.25	24.25	3.25
3010AC	7	3	21	4.0"	2.0"	100 ft.	84.25	24.25	3.25
3010AD	8	3	24	4.0"	2.0"	100 ft.	96.25	24.25	3.25

Color Options

Default color is red		Green over red (G25R)		Blue over red (B25R)		Red over Blue (R25B)	
Red over green (R25G)		Green over green (G25G)		Blue over green (B25G)		Green over Blue (G25B)	
Red over yellow (R25Y)		Green over yellow (G25Y)		Blue over yellow (B25Y)		Blue over blue (G25B)	



Email: sales@brgproducts.com
 Web Site: <http://www.brgproducts.com>

Copyright 2016, BRG Precision Products. All rights reserved. Printed in the USA, 3010 Spec Sheet Rev. 1.4.07.12.2016



600 N River Street • Derby, Kansas 67037
 800-295-0220 • 316-788-2000
 Fax: 316-788-7080