



368 Style Time Zone Clock



368B - 1.2" date, 1.8" time,
0.75" zone labels



368C - 1.2" date, 1.8" time,
0.75" zone labels



368H - 1.2" date, 1.8" time,
0.75" zone labels

The 368 series time zone clocks has a dot matrix LED date, bar-segment LED time displays with white vinyl zone labels. The date can be arranged in any format and can include Julian dates. For instance you could have 14 APR 08 or FRI APR 14. The 368 models display between 2 and 10 time zones.

Each 368 clock comes standard with an OCXOA oscillator, which is accurate to .06 seconds per year.

For easy clock management, an infrared (IR) remote control is included with every 368 model. You can specify a radio (RF) remote, if preferred for no additional charge. Every 368 model includes your choice of an Ethernet or USB interface for easy time zone parameter control.

Features:

- OCXOA oscillator accurate to .06 seconds per year
- 1.2" or 2.0" red dot matrix LEDs for displaying the date* (blue, green & yellow optional)
- 1.8", 2.5" or 4.0" red bar segment LEDs for displaying time* (blue & green optional)
- 0.75", 1.0" or 1.5" white vinyl letters for displaying zone names*
- Models that display from 2 to 10 time zones
- 12 or 24 hour format
- DST and time zone offsets supported
- PC Interface: USB Interface
- IR remote control standard or optional RF remote
- Black brushed Aluminum frame
- Multiple cord lengths available
- US, British, Australian or European plugs
- 100-240 VAC, 50-60 cycle power
- Available on GSA, contract GS-02F-0030U

*See individual model number for details.



Oven Controlled Crystal Oscillator A (OCXOA)

- 0.2 Parts per Billion (PPB)
- Accurate to .06 seconds per year
- 1 hundred times more accurate than most competing clocks
- Eliminates the need for GPS or Network time synchronization

368 Style Time Zone Clocks

Model	Zones	Displays		White Vinyl Label	Viewing Distance	Dimensions		
		Time	Date			H	W	D
368A	2	1.8"	1.2"	0.75"	40 ft.	15.25	13.25	3.25
368B	3	1.8"	1.2"	0.75"	40 ft.	21.25	13.25	3.25
368C	4	1.8"	1.2"	0.75"	40 ft.	27.25	13.25	3.25
368D	5	1.8"	1.2"	0.75"	40 ft.	33.25	13.25	3.25
368E	6	1.8"	1.2"	0.75"	40 ft.	39.25	13.25	3.25
368F	7	1.8"	1.2"	0.75"	40 ft.	45.25	13.25	3.25
368G	8	1.8"	1.2"	0.75"	40 ft.	51.25	13.25	3.25
368H	9	1.8"	1.2"	0.75"	40 ft.	57.25	13.25	3.25
368I	10	1.8"	1.2"	0.75"	40 ft.	63.25	13.25	3.25

368J	2	2.5"	2.0"	1.00"	75 ft.	20.25	20.25	3.25
368K	3	2.5"	2.0"	1.00"	75 ft.	28.25	20.25	3.25
368L	4	2.5"	2.0"	1.00"	75 ft.	36.25	20.25	3.25
368M	5	2.5"	2.0"	1.00"	75 ft.	44.25	20.25	3.25
368N	6	2.5"	2.0"	1.00"	75 ft.	52.25	20.25	3.25
368O	7	2.5"	2.0"	1.00"	75 ft.	60.25	20.25	3.25
368P	8	2.5"	2.0"	1.00"	75 ft.	68.25	20.25	3.25

368Q	2	4.0"	2.0"	1.50"	100 ft.	24.25	20.25	3.25
368R	3	4.0"	2.0"	1.50"	100 ft.	34.25	20.25	3.25
368S	4	4.0"	2.0"	1.50"	100 ft.	44.25	20.25	3.25
368T	5	4.0"	2.0"	1.50"	100 ft.	54.25	20.25	3.25
368U	6	4.0"	2.0"	1.50"	100 ft.	64.25	20.25	3.25

Color Options

Red LEDs with white zone labels is standard



Blue LEDs with white zone labels is optional



Green LEDs with white zone labels is optional



Email: sales@brgproducts.com
Web Site: <http://www.brgproducts.com>

Copyright 2015, BRG Precision Products. All rights reserved. Printed in the USA, 368 Spec Sheet.05.13.15



600 N River Street • Derby, Kansas 67037
800-295-0220 • 316-788-2000
Fax: 316-788-7080