



668 Style Time Zone Clock



Model 668G - 1.8" time, 1.2" date, 0.75" zone labels, 3 zones



Model 668I - 1.8" time, 1.2" date, 0.75" zone labels, 5 zones

The 668 series time zone clocks have either a 10 or 20 character dot matrix LEDs for the date above the bar-segment LED time displays with white vinyl zone labels below. 668 models can display between 1-10 time zones. The date can be arranged in any format and can include Julian dates. For instance you could have 14 APR 08 or FRI APR 14.

Each 668 clock comes standard with an OCXO oscillator, which is accurate to .06 seconds per year.

For easy clock management, an infrared (IR) remote control is included with every 668 model. You can specify a radio (RF) remote, if preferred for no additional charge.

Features:

- OCXO oscillator accurate to .06 seconds per year
- 1.2" or 2.0" 10 or 20 character red dot matrix date display* (blue, green & yellow optional)
- 1.8", 2.5" or 4.0" red bar segment LEDs for displaying time* (blue & green optional)
- 0.75", 1.0" or 1.5" white vinyl lettering for displaying zone names*
- Models that display from 1 to 10 separate time zones*
- 12 or 24 hour format
- DST and time zone offsets supported
- IR remote control standard or optional RF remote
- Black brushed Aluminum frame
- Multiple cord lengths available
- US, British, Australian or European plugs
- 100-240 VAC. 50-60 cycle power
- Available on GSA, contract GS-02F-0030U

*See individual model number for details.



Oven Controlled Crystal Oscillator (OCXO)

- Accurate to 2 PPB (parts per Billion) or .06 seconds per year or about 1 second in 20 years.
- 1 thousand times more accurate than most competing clocks
- Eliminates the need for GPS or Network time synchronization for

668 Style Time Zone Clocks

Model	Zones	Displays			White Vinyl Labels	Viewing Distance	Dimensions		
		Time	Date	Digits			H	W	D
668A	2	1.8"	1.2"	10	0.75"	40 ft.	9.25	20.25	3.25
668P	2	1.8"	1.2"	20	0.75"	40 ft.	9.25	26.25	3.25
668B	3	1.8"	1.2"	10	0.75"	40 ft.	9.25	30.25	3.25
668G	3	1.8"	1.2"	20	0.75"	40 ft.	9.25	30.25	3.25
668H	4	1.8"	1.2"	20	0.75"	40 ft.	9.25	40.25	3.25
668I	5	1.8"	1.2"	20	0.75"	40 ft.	9.25	50.25	3.25
668Q	6	1.8"	1.2"	20	0.75"	40 ft.	9.25	60.25	3.25
668R	7	1.8"	1.2"	20	0.75"	40 ft.	9.25	70.25	3.25
668S	8	1.8"	1.2"	20	0.75"	40 ft.	9.25	80.25	3.25
668AA	9	1.8"	1.2"	20	0.75"	40 ft.	9.25	90.25	3.25
668AB	10	1.8"	1.2"	20	0.75"	40 ft.	9.25	96.25	3.25
668C	2	2.5"	2.0"	10	1.00"	75 ft.	12.25	24.25	3.25
668T	2	2.5"	2.0"	20	1.00"	75 ft.	12.25	39.25	3.25
668D	3	2.5"	2.0"	10	1.00"	75 ft.	12.25	36.25	3.25
668J	3	2.5"	2.0"	20	1.00"	75 ft.	12.25	39.25	3.25
668K	4	2.5"	2.0"	20	1.00"	75 ft.	12.25	48.25	3.25
668L	5	2.5"	2.0"	20	1.00"	75 ft.	12.25	60.25	3.25
668U	6	2.5"	2.0"	20	1.00"	75 ft.	12.25	72.25	3.25
668V	7	2.5"	2.0"	20	1.00"	75 ft.	12.25	84.25	3.25
668W	8	2.5"	2.0"	20	1.00"	75 ft.	12.25	96.25	3.25
668E	2	4.0"	2.0"	10	1.50"	100 ft.	14.25	30.25	3.25
668X	2	4.0"	2.0"	20	1.50"	100 ft.	14.25	39.25	3.25
668F	3	4.0"	2.0"	10	1.50"	100 ft.	14.25	45.25	3.25
668M	3	4.0"	2.0"	20	1.50"	100 ft.	14.25	45.25	3.25
668N	4	4.0"	2.0"	20	1.50"	100 ft.	14.25	60.25	3.25
668O	5	4.0"	2.0"	20	1.50"	100 ft.	14.25	75.25	3.25
668Y	6	4.0"	2.0"	20	1.50"	100 ft.	14.25	90.25	3.25
668Z	7	4.0"	2.0"	20	1.50"	100 ft.	14.25	96.25	3.25

Color Options

Red LEDs with white zone labels is standard



Blue LEDs with white zone labels is optional



Green LEDs with white zone labels is optional



Email: sales@brgproducts.com
 Web Site: <http://www.brgproducts.com>

Copyright 2016, BRG Precision Products, All rights reserved. Printed in the USA, #68 Spec Sheet Rev. 1.2.01.27.2016



600 N River Street • Derby, Kansas 67037
 800-295-0220 • 316-788-2000
 Fax: 316-788-7080