

7710 Style Time Zone Clock



Model 7710E - 1.8" time, 15 character - 1.2" zone labels, 5 zones

The 7710 series time zone clocks have bar-segment LED time displays with fifteen character dot matrix digital zone labels below. In many 7710 models, the clock can display up to 16 time zones through page flipping. For example, a five zone clock can show three pages of time zone information. Likewise, a three zone unit can show five pages.

Each 7710 clock comes standard with an OCXO oscillator, which is accurate to .06 seconds per year.

For easy clock management, an infrared (IR) remote control is included with every 7710 model. You can specify a radio (RF) remote, if preferred for no additional charge. Every 7710 model includes your choice of an Ethernet or USB interface for easy time zone parameter control.

Features:

- OCXO oscillator accurate to .06 seconds per year
- 1.8", 2.5" or 4.0" red bar segment LEDs for displaying time* (blue & green optional)
- 1.2" or 2.0" red 15 character alpha numeric dot matrix LEDs for displaying zone names* (blue, green & yellow optional)
- Models that display from 1 to 5 separate time zones
- Zone flipping feature that allows up to 16 zones in a single clock*
- 12 or 24 hour format
- DST and time zone offsets supported
- PC Interface: USB Interface
- IR remote control standard or optional RF remote
- Black brushed Aluminum frame
- Multiple cord lengths available
- US, British, Australian or European plugs
- 100-240 VAC. 50-60 cycle power
- Available on GSA, contract GS-02F-0030U

*See individual model number for details.



Oven Controlled Crystal Oscillator (OCXO)

- 0.2 Parts per Billion (PPB)
- Accurate to .06 seconds per year
- 1 hundred times more accurate than most competing clocks
- Eliminates the need for GPS or Network time synchronization

7710 Style Time Zone Clocks



Model 7710G -2.5" time, 15 character 1.2" zone labels & date, 2 zones

Model	Physical Positions	Maximum		Displays		Viewing Distance	Dimensions		
		Pages	Zones	Time	Label		H	W	D
7710A	1	17	17	1.8"	1.2"	40 ft.	7.25	18.25	3.25
7710B	2	8	16	1.8"	1.2"	40 ft.	7.25	36.25	3.25
7710C	3	5	15	1.8"	1.2"	40 ft.	7.25	54.25	3.25
7710D	4	4	16	1.8"	1.2"	40 ft.	7.25	72.25	3.25
7710E	5	3	15	1.8"	1.2"	40 ft.	7.25	90.25	3.25

7710F	1	17	17	2.5"	1.2"	75 ft.	8.25	18.25	3.25
7710G	2	8	16	2.5"	1.2"	75 ft.	8.25	36.25	3.25
7710H	3	5	15	2.5"	1.2"	75 ft.	8.25	54.25	3.25
7710I	4	4	16	2.5"	1.2"	75 ft.	8.25	72.25	3.25
7710J	5	3	15	2.5"	1.2"	75 ft.	8.25	90.25	3.25

7710K	1	17	17	4.0"	1.2"	75 ft.	10.25	18.25	3.25
7710L	2	8	16	4.0"	1.2"	75 ft.	10.25	36.25	3.25
7710M	3	5	15	4.0"	1.2"	75 ft.	10.25	54.25	3.25
7710N	4	4	16	4.0"	1.2"	75 ft.	10.25	72.25	3.25
7710O	5	3	15	4.0"	1.2"	75 ft.	10.25	90.25	3.25

7710P	1	17	17	4.0"	2.0"	100 ft.	12.25	29.25	3.25
7710Q	2	8	16	4.0"	2.0"	100 ft.	12.25	58.25	3.25
7710R	3	5	15	4.0"	2.0"	100 ft.	12.25	87.25	3.25

Color Options

Default color is red		Green over red (G25R)		Blue over red (B25R)		Red over Blue (R25B)	
Red over green (R25G)		Green over green (G25G)		Blue over green (B25G)		Green over Blue (G25B)	
Red over yellow (R25Y)		Green over yellow (G25Y)		Blue over yellow (B25Y)		Blue over blue (G25B)	



Email: sales@brgproducts.com
 Web Site: <http://www.brgproducts.com>

Copyright 2016, BRG Precision Products, All rights reserved, Printed in the USA, 7710 Rev1.2.07.12.2016



600 N River Street • Derby, Kansas 67037
 800-295-0220 • 316-788-2000
 Fax: 316-788-7080