|   | North America - Toll Free 800.295.0220<br>International - 316.788.2000   |
|---|--|
| BRG   | 7710DCCCD Time Zone Clock  |
| PRECISION<br>PRODUCTS   |  |
| www.brgprecsion.com   |  |
| User Changeable Multi-Color LED Colors  8898 0835 0835 0835 0835 0835 0835 0835 083   |  |
| PEARL HARBOR FORT WAINWRIGHT MCAS MIRAMAR SPACE FORCE MCCONNELL AFB WASHINGTON DC ZULU - GMT  |  |
| 8588<br>FRANKFURT GER   | 3535     3835     3835     3835       WARSAW POLAND     KYIV-UKRAINEL     KUWAIT CITY     DOHO @ATAR     BAGHDAD IRAQ  |
|   | 1905 2235 2235 8038<br>AFGHANISTAN SINGAPORE BEIJING CHINA ANDERSEN AFB  |
| Specifications  | Model 7710DCCCD- 1.8" time, 1.2" - 15 character zone labels, 17 zones  |
| Display:  | Seventeen zone, 7 segment user changeable multi-color bar segment LED time displays with 1.2" - 15 character dot matrix LED zone labels.   |
| Zone Capacity:  | Up to 17 time zones can be displayed by page flipping zones 1 time   |
| Display Format:   | 12 or 24 hour format. Alpha-numeric date is custom configurable in up to four languages (English, French, German & Spanish). Alpha dates, Julian dates and year formats can be laid out in any order Numeric Year, and Julian Date |
| Clock Accuracy:   | BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required.  |
| Computer Interface:   | USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.  |
| Manual Controls:  | Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.  |
| Operating Mode:   | Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.  |
| Digit Height:   | 1.8" bar segment LEDs for time, 1.2" dot matrix LEDs for zone labels alpha-numeric date.   |
| Visibility:   | Up to 40 feet  |
| Power Requirement:  | 100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.  |
| Dimensions:   | 7.25" Tall x 307.25" Wide x 3.25" Deep   |
| Operating Temperature:  | -32° F to 120°F  |
| Humidity:   | 0% to 95% Non-condensing   |
| Construction:   | Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.  |
| User Changeable Multi-Color LED Colors  |  |
| Image: Contract in the second state |  |



Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2023, BRG Precision Products, All rights reserved, 7710DCCCD Spec Sheet Rev 1.1 03.06.2023

Green

Red



Magenta

Cyan

White

Yellow

Blue

600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080