User Changeable Multi-Color LED Colors



Model 7710NN - 4.0" time, 1.2" - 15 character zone labels, 8 zones

Specifications

| Display: | Eight zone, 7 segment user changeable multi-color bar segment LED time displays with 1.2" - 15 character dot matrix LED zone labels and alpha-numeric date. |
|---|--|
| Zone Capacity: | Up to 16 time zones can be displayed by page flipping zones 2 times |
| Display Format: | 12 or 24 hour format. Alpha-numeric date is custom configurable in up to four languages (English, French, German & Spanish). Alpha dates, Julian dates and year formats can be laid out in any order Numeric Year, and Julian Date |
| Clock Accuracy: | BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required. |
| Computer Interface: | USB interface is standard, Ethernet interface is available in lieu of the USB at no cost. |
| Manual Controls: | Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options. |
| Operating Mode: | Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets. |
| Digit Height: | 4.0" bar segment LEDs for time, 1.2" dot matrix LEDs for zone labels alpha-numeric date. |
| Visibility: | Up to 75 feet |
| Power Requirement: | 100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard. |
| Dimensions: | 10.25" Tall x 144.5" Wide x 3.25" Deep |
| Operating Temperature: | -32° F to 120°F |
| Humidity: | 0% to 95% Non-condensing |
| Construction: | Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included. |
| User Changeable Multi-Color LED Colors | |
| I | |



Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2022, BRG Precision Products, All rights reserved, 7710NN Spec Sheet Rev 1.0 08.24.2022

Green

Blue

Red

BRG

Magenta

Cyan

White

Yellow

600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080