## 6612M Time Zone Clock

www.brgprecsion.com

## User Changeable Multi-Color LED Colors



Model 6612M - 4.0" time, 2.0" zone labels, 4 zones

## **Specifications**

| Display:               | 6 zone, 5 digit user changeable multi-color bar segment LED time displays with 10 character dot matrix LED zone labels.   |
|------------------------|---|
| Zone Capacity:         | Up to 24 time zones can be displayed by page flipping zones 4 times   |
| Display Format:        | 12 or 24 hour format, Numeric Date, (American or European), Numeric Year, and Julian Date   |
| Clock Accuracy:        | BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required. |
| Computer Interface:    | USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.   |
| Manual Controls:       | Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.   |
| Operating Mode:        | Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.   |
| Digit Height:          | 4.0" bar segment LEDs for time, 2.0" dot matrix LEDs for zone labels.   |
| Visibility:            | Up to 100 feet  |
| Power Requirement:     | 100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.   |
| Dimensions:            | 24.25" Tall x 60.25" Wide x 3.25" Deep  |
| Operating Temperature: | -32° F to 120°F   |
| Humidity:              | 0% to 95% Non-condensing  |
| Construction:          | Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.   |
|                        | lister Ober weekin Melff Osland ED Osland   |





Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2022, BRG Precision Products, All rights reserved, 6612M Spec Sheet Rev 1.0 09.13.2022



600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080