

3420N Time Zone Clock

www.brgprecsion.com

Specifications

•	
Display:	Six zone, 4 digit user changeable multi-color bar segment LED time displays with 10 character dot matrix LED zone labels.
Zone Capacity:	Up to 24 time zones can be displayed by page flipping zones 4 times.
Display Format:	12 or 24 hour format. (American or European). Numeric Year, and Julian Date
Clock Accuracy:	BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required.
Computer Interface:	USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.
Manual Controls:	Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.
Operating Mode:	Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.
Digit Height:	2.5" bar segment LEDs for time, 2.0" dot
Visibility:	Up to 75 feet

User Changeable Multi-Color LED Colors



Model 3420N - 2.5" time, 2.0" zone labels, 6 zones

	•
Operating Mode:	Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.
Digit Height:	2.5" bar segment LEDs for time, 2.0" dot matrix LEDs for zone labels.
Visibility:	Up to 75 feet
Power Requirement:	100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.
Dimensions:	36.25" Tall x 32.25" Wide x 3.25" Deep
Operating Temperature:	-32° F to 120°F
Humidity:	0% to 95% Non-condensing
Construction:	Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.
	User Changeable Multi-Color LED Colors



Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2022, BRG Precision Products, All rights reserved, 3420N Spec Sheet Rev 1.0 09.21.2022

Red

09:07

Green

PACIFIC

Blue

IN CENTRAL EASTERN Yellow Magenta

1 1:0 1



17:0 1

Cyan

18:0 1

GERMANY

White

600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080