International - 316.788.2000 6610NMN Time Zone Clock www.brgprecsion.com User Changeable Multi-Color LED Colors $\{4; 45\}$ MOUNTAIN Model 6610NMN - 4.0" time, 2.0" zone labels, 3 modules, 11 zones Specifications Display: Three individual time zone sections that make up a 11 zone, 4 digit user changeable multicolor bar segment LED time displays with 10 character dot matrix LED zone labels. Zone Capacity: Up to 22 time zones can be displayed by page flipping zones 2 times **Display Format:** 12 or 24 hour format, Numeric Date, (American or European), Numeric Year, and Julian Date BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized **Clock Accuracy:** with the Atomic Clock, no external synchronization methods are required. Computer Interface: USB interface is standard, Ethernet interface is available in lieu of the USB at no cost. Manual Controls: Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options. **Operating Mode:** Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets. **Digit Height:** 4.0" bar segment LEDs for time, 2.0" dot matrix LEDs for zone labels. Visibility: Up to 100 feet Power Requirement: 100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard. **Dimensions:** 12.25" Tall x 220.75" Wide x 3.25" Deep Operating Temperature: -32° F to 120°F Humidity: 0% to 95% Non-condensing

North America - Toll Free 800.295.0220

Construction: Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.

User Changeable Multi-Color LED Colors							
07:01 HAWAII	0901 PACIFIC	10:01 MOUNTAIN	/ /:// / Central	12:0 1 Eastern	/ 7:☐ / ZULU	18:0 1 GERMANY	
Red	Green	Blue	Yellow	Magenta	Cyan	White	
Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2024, BRG Precision Products, All rights reserved, 6610NMN Spec Sheet Rev 1.1 03.12.2024			BRG		600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080		