## 6612I Time Zone Clock

## www.brgprecsion.com

## User Changeable Multi-Color LED Colors

<b>8 8:4 5</b>	B:45	HOUNTAIN	1 :46	12:46
Alaska	PACIFIC		CENTRAL	EASTERN
1 <b>5:45</b>	17:45	0 1:45	CHAMORRO	02:46
zulu	LONDON	JAPAN		AUSTRALIA

Model 6612I - 2.5" time, 1.2" zone labels, 10 zones
---

## **Specifications**

Display:	10 zone, 5 digit user changeable multi-color bar segment LED time displays with 10 character dot matrix LED zone labels.		
Zone Capacity:	Up to 20 time zones can be displayed by page flipping zones 2 times		
Display Format:	12 or 24 hour format, Numeric Date, (American or European), Numeric Year, and Julian Date		
Clock Accuracy:	BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchron with the Atomic Clock, no external synchronization methods are required.		
Computer Interface:	USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.		
Manual Controls:	Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.		
Operating Mode:	Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.		
Digit Height:	2.5" bar segment LEDs for time, 1.2" dot matrix LEDs for zone labels.		
Visibility:	Up to 75 feet		
Power Requirement:	100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.		
Dimensions:	16.25" Tall x 65.25" Wide x 3.25" Deep		
Operating Temperature:	-32° F to 120°F		
Humidity:	0% to 95% Non-condensing		
Construction:	Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.		
	lleer Channachte Multi Calart ED Calare		

User Changeable Multi-Color LED Colors

Yellow



Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2022, BRG Precision Products, All rights reserved, 66121 Spec Sheet Rev 1.0 09.13.2022

Red

Green

Blue



Magenta

Cyan

White

600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080