## 6613G Time Zone Clock

www.brgprecsion.com

## User Changeable Multi-Color LED Colors

18:35	00:35	0 #35	02:35
LOCAL	ZULU	GERMANY	TURKEY
1 105	1 105	<i>† 11</i> 05	1 1105

Model 6613G - 2.5" bar segment time & date, 1.2" zone labels, 4 zones

## **Specifications**

Display:	Four zone, 4 digit user changeable multi-color bar segment LED time and date displays with 10 character dot matrix LED zone labels.		
Zone Capacity:	Up to 12 time zones can be displayed by page flipping zones 3 times		
Display Format:	12 or 24 hour format, Numeric Date, (American or European), Numeric Year, and Julian Date		
Clock Accuracy:	BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required.		
Computer Interface:	USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.		
Manual Controls:	Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.		
Operating Mode:	Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.		
Digit Height:	2.5" bar segment LEDs for the time and date, 1.2" 10 character dot matrix LEDs for zone labels.		
Visibility:	75 feet		
Power Requirement:	100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.		
Dimensions:	14.25" Tall x 52.25" Wide x 3.25" Deep		
Operating Temperature:	-32° F to 120°F		
Humidity:	0% to 95% Non-condensing		
Construction:	Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.		
User Changeable Multi-Color LED Colors			



Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2022, BRG Precision Products, All rights reserved, 6613G Spec Sheet Rev 1.0 09.19.2022

Red

09:01

PACIFIC

Blue

Green



Magenta

17:0 1

Cyan

18:0 1

GERMANY

White

/ /:// / CENTRAL

Yellow

600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080