6613R Time Zone Clock

www.brgprecsion.com

User Changeable Multi-Color LED Colors

19:45	17.45	1040	ρ <u>n</u> uc	DUNC	2240	nius	0245
		LANDSTUHL					
29109	2909	2909	29189	29109	2909	3009	3009

Model 6613R - 2.5" bar segment time & date, 1.2" zone labels, 8 zones

Specifications

Display:	Eight zone, 4 digit user changeable multi-color bar segment LED time and date displays with 10 character dot matrix LED zone labels.				
Zone Capacity:	Up to 8 time zones can be displayed by page flipping zones 1 time				
Display Format:	12 or 24 hour format, Numeric Date, (American or European), Numeric Year, and Julian Date				
Clock Accuracy:	BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required.				
Computer Interface:	USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.				
Manual Controls:	Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.				
Operating Mode:	Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.				
Digit Height:	2.5" bar segment LEDs for the time and date, 1.2" 10 character dot matrix LEDs for zone labe				
Visibility:	75 feet				
Power Requirement:	100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.				
Dimensions:	14.25" Tall x 99.25" Wide x 3.25" Deep				
Operating Temperature:	-32° F to 120°F				
Humidity:	0% to 95% Non-condensing				
Construction:	Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.				
User Changeable Multi-Color LED Colors					



Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2022, BRG Precision Products, All rights reserved, 6613R Spec Sheet Rev 1.0 09.19.2022

Red

09:01

Green

PACIFIC

Blue



Magenta

17:0 1

Cyan

18:0 1

GERMANY

White

/ /:// / CENTRAL

Yellow

600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080