www.brgprecsion.com

User Changeable Multi-Color LED Colors



Model 6673E - 2.5" time, 1.2" zone labels, 1.2" dot matrix alpha-numeric date, 2 zones

Specifications

Display:	Two zone, 7 segment user changeable multi-color bar segment LED time displays with 1.2" - 10 character dot matrix LED zone labels and alpha-numeric date.
Zone Capacity:	Up to 12 time zones can be displayed by page flipping zones 6 times
Display Format:	12 or 24 hour format. Alpha-numeric date is custom configurable in up to four languages (English, French, German & Spanish). Alpha dates, Julian dates and year formats can be laid out in any order Numeric Year, and Julian Date
Clock Accuracy:	BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required.
Computer Interface:	USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.
Manual Controls:	Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.
Operating Mode:	Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.
Digit Height:	2.5" bar segment LEDs for time, 1.2" dot matrix LEDs for zone labels alpha-numeric date.
Visibility:	Up to 75 feet
Power Requirement:	100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.
Dimensions:	11.25" Tall x 26.25" Wide x 3.25" Deep
Operating Temperature:	-32° F to 120°F
Humidity:	0% to 95% Non-condensing
Construction:	Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.
_	User Changeable Multi-Color LED Colors



Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2022, BRG Precision Products, All rights reserved, 6673E Spec Sheet Rev 1.0 08.09.2022

Red

09:01

Green

PACIFIC

Blue



Magenta

17:0 1

Cyan

18:0 1

GERMANY

White

1 1:0 1

CENTRAL

Yellow

600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080