6789S Time Zone Clock With Date and Scrolling Message Display

www.brgprecsion.com

User Changeable Multi-Color LED Colors

THU 01 SEP 2022 244							
	20110	20:15 GERMANY	20:15 NORWAY	2 :15 MOSCOW	03:15 OKINAWA	08:15 HAWAII	1 1:15 CALIFORNIA
II MIG SUPPLY							
Model 6789S - 1.8" time, 1.2" zone labels, 1.2" 20 character date 2.0" dot matrix message display 72" wide, 8 zones							
Specificat	ions	2.0 dot matrix message display 12 wide, 0 20nes					
Dia		Fight sons 4 disit		le multi eelen ha		time displayer	
Dis	splay:	Eight zone, 4 digit user changeable multi-color bar segment LED time displays with 10 character dot matrix LED zone labels, 20 character date and 2" x 72" scrolling message disp					
Zone Cap	oacity:	Up to 16 time zones can be displayed by page flipping zones 2 times					
Display Fo	ormat:	12 or 24 hour format. Alpha-numeric date is custom configurable in up to four languages (English, French, German & Spanish). Alpha dates, Julian dates and year formats can be laid out in any order Numeric Year, and Julian Date					
Message Dis	splay:	The PC interface or optional Time Commander is required to make any changes to the message display. The included IR1 remote control is not connected to the message display.					
Clock Accu	uracy:	BRG Time Zone Clocks will display the correct time for the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required.					
Computer Inter	rface:	USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.					
Manual Cor	ntrols:	Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.					
Operating N	Mode:	Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.					
Digit H	eight:	1.8" bar segment LEDs for time, 1.2" dot matrix LEDs for zone labels, 1.2" 20 character date and 2.0" LEDs for message display.					
Visi	ibility:	Up to 40 feet					
Power Require	ment:	100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.					
Dimens	sions:	16.25" Tall x 99.25" Wide x 3.25" Deep					
Operating Tempera	ature:	-32° F to 120°F					
Hum	nidity:	0% to 95% Non-condensing					
Constru	iction:	Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.					



Email: sales@brgproducts.com Web Site: https://www.brgprecision.com Copyright 2023, BRG Precision Products, All rights reserved, 6789S Spec Sheet Rev 1.1 09.13.2023 BRG

600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080