www.brgprecsion.com

## User Changeable Multi-Color LED Colors



Model 6618X - 4.0" time, 2.0" zone labels, 2.0" 20 Character Date, 2 zones

Specifications	
Display:	Two zone, 5 digit user changeable multi-color bar segment LED time displays with 10 character dot matrix LED zone labels and 20 character date.
Zone Capacity:	Up to 16 time zones can be displayed by page flipping zones 8 times
Display Format:	12 or 24 hour format. Alpha-numeric date is custom configurable in up to four languages (English, French, German & Spanish). Alpha dates, Julian dates and year formats can be laid out in any order Numeric Year, and Julian Date
Clock Accuracy:	BRG Time Zone Clocks will display the correct time tor the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required.
Computer Interface:	USB interface is standard, Ethernet interface is available in lieu of the USB at no cost.
Manual Controls:	Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.
Operating Mode:	Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.
Digit Height:	4.0" bar segment LEDs for time, 2.0" dot matrix LEDs for zone labels and 2.0" dot matrix date.
Visibility:	Up to 100 feet
Power Requirement:	100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.
Dimensions:	16.25" Tall x 45.25" Wide x 3.25" Deep
Operating Temperature:	-32° F to 120°F
Humidity:	0% to 95% Non-condensing
Construction:	Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.
	User Changeable Multi-Color LED Colors



Email: <u>sales@brgproducts.com</u> Web Site: <u>https://www.brgprecision.com</u>	
Copyright 2022, BRG Precision Products, All rights reserved, 6618X Spec Sheet Rev 1.0 07.26.2022	

Red

09:01

Green

PACIFIC

Blue



Magenta

17:01

Cyan

18:0 1

GERMANY

White

1 1:0 1

CENTRAL

Yellow

600 N River Street • Derby, Kansas 67037 800-295-0220 • 316-788-2000 Fax: 316-788-7080