



689P Time Zone Clock

With Date and Scrolling Message Display

www.brgprecision.com

User Changeable Multi-Color LED Colors



Model 689P - 2.5" time, 1.0" vinyl zone labels, 2.0" 20 character date
2.0" dot matrix message display 60" wide, 6 zones

Specifications

Display:	Five zone, 4 digit user changeable multi-color bar segment LED time displays with 1.0" white vinyl zone labels, 20 character date and 2"x 60" scrolling message display.
Display Format:	12 or 24 hour format. Alpha-numeric date is custom configurable in up to four languages (English, French, German & Spanish). Alpha dates, Julian dates and year formats can be laid out in any order Numeric Year, and Julian Date
Message Display:	The PC interface or optional Time Commander is required to make any changes to the message display. The included IR1 remote control is not connected to the message display.
Clock Accuracy:	BRG Time Zone Clocks will display the correct time for the life of the clock. Factory synchronized with the Atomic Clock, no external synchronization methods are required.
Manual Controls:	Wireless IR Remote Control Included. USB-IR fob and Time Commander graphical remote control programmer are available options.
Operating Mode:	Time zones with 11 Daylight Saving automatic adjustments and 5 incremental offsets.
Digit Height:	2.5" bar segment LEDs for time, 2.0" 20 character date and 2.0" LEDs for message display.
Visibility:	Up to 75 feet
Power Requirement:	100-240 volts AC, 50-60 cycle, internal transformer, 12 ft cord standard with US plug standard.
Dimensions:	18.25" Tall x 72.25" Wide x 3.25" Deep
Operating Temperature:	-32° F to 120° F
Humidity:	0% to 95% Non-condensing
Construction:	Black anodized Aluminum frame with plexiglass front lens. Mounting hardware included.

User Changeable Multi-Color LED Colors



Email: sales@brgproducts.com
Web Site: <https://www.brgprecision.com>

Copyright 2023, BRG Precision Products, All rights reserved,
689P Spec Sheet Rev 1.1 09.12.20223



600 N River Street • Derby, Kansas 67037
800-295-0220 • 316-788-2000
Fax: 316-788-7080